

www.creativematerials.com

ISO 9001 CERTIFIED

Creative Materials, Inc. 12 Willow Road Ayer, MA 01432

т 978.391.4700 F 978.391.4705

119-36

PAD-PRINTABLE, PLATEABLE, ELECTRICALLY CONDUCTIVE INK

DESCRIPTION: 119-36 is a pad-printable, electrically conductive ink and coating which is suitable for applications requiring subsequent electroless plating operations. The product features excellent adhesion to Kapton, Mylar, glass and a variety of other substrates. Unlike conventional conductive materials, this product is very resistant to abrasion, scratching and thermal aging. Some applications for 119-36 include, but are not limited to, electroless, plating, anode and cathode coatings for capacitors, and as an underlying coating for decorative plating on various substrates.

TYPICAL PROPERTIES:

| Viscosity (cps) | 10,000-12,000 |
|--------------------------------------|---------------|
| Filler | Silver |
| Percent Silver (cured) | > 70 |
| Volume Resistance, max. (Ω-cm) | 0.002 |
| Sheet Resistivity, max. (Ω/sq./mil.) | 0.08 |
| Solderable | No |
| Hydrolytic Stability | Excellent |
| Useful Temperature Range (°C) | -55 to 200 |
| Thermal Stability (°C) | Good to 325 |

SUGGESTED HANDLING & CURING: 119-36 is ready to use as supplied. Further thinning may be accomplished by adding small amounts of CMI Thinner #113-39 or for slower drying CMI Thinner # 114-20. Prior to using, be certain to resuspend silver. Best properties, for most applications, result when cured for 1 hour at 175°C. Good properties are obtained on a variety of substrates by curing at temperatures ranging from 50°C to 150°C. End user is advised to experimentally determine temperature and time best suited for individual applications.

STORAGE: Shelf life: 1 month at 25°C; or 3 months at -10°C.

SAFETY & HANDLING: Use with adequate ventilation. Keep away from sparks and open flames. Avoid prolonged contact with skin and breathing of vapors. Wash with soap and water to remove from skin.